

METAL BELLOW DOUBLE CARTRIDGE MECHANICAL SEAL (INBOARD BELLOW/OUTBOARD NON-BELLOW TYPE)

TYPE : BD740

Face Materials :

- Carbon / Silicon Carbide / Tungsten Carbide

Secondary Seals :

- Grafoil / PTFE / Kalrez

Hardware :

- SS 316L / Hastelloy-B & C / Alloy-20 / Titanium

Bellow Material :

- AM-350 / Alloy 20 / Hastelloy-C / Inconel 625 / Titanium

Operating Limits :

Size : 25 mm to 150 mm

Pressure : 25 bars

Temperature : -20 to +350 Deg. C

Speed : 2900 RPM

Application :

- Fatty Acid
- LPG Plants
- Power Plants
- Thermic Fluid
- Hydrocarbons
- Hazardous Liquid
- High Temperature
- Oil & Gas Industries
- Refining Technology
- Chemicals Industries
- Petrochemical Industries
- Biochemistry & Hot Oil Process Pump



Features :

- Double Seal
- Rotary Spring Type
- Double Cartridge Design
- Factory Assembled & Tested
- Metric And Inch Sizes Available
- Quick Installation & Easy Removal
- Independent of Direction of Rotation
- Come with connection of Cooling Arrangement