

Multi Spring Semi-Cartridge Mechanical Seal (Balance & Un-balance Type)

TYPE : SSC697A-G

Face Materials :

- Carbon / Ceramic / Silicon Carbide / Tungsten Carbide

Secondary Seals :

- Nitrile (NBR) / Viton (FKM) / EPDM / Aflas / Neoprene / PTFE / TTV / Kalrez (FFKM)

Hardware :

- SS 304 / SS 316 / Duplex / Hastelloy-B & C / Alloy-20 / Titanium

Operating Limits :

Size: 20.0 mm to 300.0 mm (0.800" to 12.000")

Speed: 2900 rpm

Pressure: 40 bars (580 psi)

Temperature: -40 °C to +220 °C (-40 °F +428 °F)

Application :

- Beverages
- Hot Water
- Solvent Plant
- Chilling Plant
- Steel Industry
- Pumps Process
- Process Industry
- Oil & Gas Industry
- Light Hydrocarbon
- Chemicals Industry
- Vacuum Distillation
- Refining Technology
- Petrochemical Industry
- Pharmaceutical Industry
- Power Plant Technology
- Blower & Other Rotary Equipment Etc.



Multi Spring Semi-Cartridge Mechanical Seal (Balance & Un-balance Type)

Features :

- **Single Seal Design** for enhanced performance.
- Available in **Metric and Inch Sizes** for versatility.
- **Costs-Effective** due to refurbishment possibilities.
- **Hydraulically Balanced & Unbalanced** Design options.
- **Multiple Spring Type** mechanism for improved reliability.
- **Quick Installation and Easy Removal** to simplify maintenance.
- **Semi-Cartridge Construction** that is factory assembled and tested.
- **Independent of Direction of Rotation**, ensuring consistent performance.
- Available **with or without connections for Flushing and Quenching** to suit various operational needs.

➤ **DIMENSIONS FOR HIGHER SIZES AVAILABLE ON REQUEST**