

Wave Spring Semi-Cartridge Mechanical Seal (Balance & Un-balance Type)

TYPE : SSC698A-F

Face Materials :

- Carbon / Ceramic / Silicon Carbide / Tungsten Carbide

Secondary Seals :

- Nitrile (NBR) / Viton (FKM) / EPDM / Aflas / Neoprene / TTV / Kalrez (FFKM)

Hardware :

- SS 304 / SS 316 / Duplex / Hastelloy-B & C

Operating Limits :

Size : 20.0 mm to 100.0 mm (0.750" to 4.000")

Speed : 2900 rpm

Pressure : 12 bars (174 psi)

Temperature : -50°C to +180°C (-58°F +356°F)

Application :

- Hot Water
- Solvent Plant
- Chilling Plant
- Steel Industry
- Process Industry,
- Oil & Gas Industry
- Chemical Industry
- Light Hydrocarbon
- Chemical Industry
- Process Pumps Etc.
- Vacuum Distillation
- Refining Technology
- Pulp & Paper Industry
- Petrochemical Industry
- Pharmaceutical Industry
- Power Plant Technology
- Food & Beverage Industry



Wave Spring Semi-Cartridge Mechanical Seal (Balance & Un-balance Type)

Features :

- **Single Seal Design** for enhanced performance.
- Available in **Metric** and Inch **Sizes** for versatility.
- **Costs-Effective** due to refurbishment possibilities.
- **Hydraulically Balanced & Unbalanced** Design options.
- **Quick Installation and Easy Removal** to simplify maintenance.
- **Semi-Cartridge Construction** that is factory assembled and tested.
- **Independent of Direction of Rotation**, ensuring consistent performance.
- Wave spring mechanism ensuring efficient sealing **with a compact design**.
- Available **with or without connections for Flushing and Quenching** to suit various operational needs.

➤ **DIMENSIONS FOR HIGHER SIZES AVAILABLE ON REQUEST**