Gipfel Engineering

ISO 9001-2015 CERTIFIED COMPANY

API 682 Mechanical Seal (High-Integrity Sealing for Critical Equipment)

TYPE : API 682



Face Materials :

- Carbon / Silicon Carbide / Tungsten Carbide

Secondary Seals :

- NBR (Nitrile) / FKM (Viton) / EPDM / Aflas / PTFE

Hardware :

- SS 316 / SS 316L / Hastelloy C-276 / Alloy 20 / Titanium / Carpenter

Bellow Material :

- AM-350 / Alloy 20 / Hastelloy C / Inconel 625 / Titanium

Operating Limits :

Size : 20.0 mm to 150.0 mm / 0.750" to 6.000"
Speed : 3600 RPM
Pressure : Vacuum ... 35 bars (508 PSI)
Temperature : -130 °C to +400 °C (-202 °F to +752 °F)

Application :

- LPG Plant
- Biochemistry
- Hydrocarbons
- Hazardous Liquid
- Oil & Gas Industry
- Chemical Industry
- High Temperature
- Refining Technology
- Petrochemical Industry
- Power Plant Technology
- API Standard Pumps Etc.

Meet: Gala No. 7, KMC Compound, Behind Hotel Metro Palace, Behram Baug Road, Jogeshwari (West), Mumbai - 400 102. Maharashtra, India.
Talk: +91 - 22 6695 6111 / 6222 | Chat: +91 - 9967 80 40 92 / +91 - 8879 147 211
Write: office@gipfelengg.com / gipfelengg@gmail.com | Look: www.gipfelengg.com / www.gipfelengineering.in

Gipfel Engineering

ISO 9001-2015 CERTIFIED COMPANY

API 682 Mechanical Seal

(High-Integrity Sealing for Critical Equipment)

Key Advantages :

- **Global Compatibility:** Offered in both **metric and imperial (inch) sizes,** suitable for a wide range of international equipment specifications.
- **Hydraulically Balanced Seal Faces:** Reduces axial face load to minimize wear, lower heat generation, and extend operational seal life.
- **Quick Installation & Maintenance Access:** Simplified installation and removal design reduces equipment downtime and maintenance labour requirements.
- **Rotary & Stationary Metal Bellows Options:** Engineered for **durability under high temperature and corrosive conditions,** offering flexibility based on application needs.
- **Non-Directional Operation:** Capable of operating in **both clockwise and counterclockwise shaft rotations,** allowing easy installation without concern for rotation direction.
- **Factory Assembled & Performance Tested:** Delivered pre-assembled and tested for pressure integrity and compliance with **API 682** standards, ensuring immediate field reliability.
- **Integrated Flush and Quench Connections:** Fully compatible with API 682 **piping plans** (e.g., Plan 11, 32, 52, 53) for improved cooling, cleaning, and environmental control.
- **Single and Dual Seal Arrangements:** Available in **Arrangement 1 (single), 2 (tandem), and 3 (double pressurized)** configurations to meet a range of containment and safety requirements.
- **Flexible Spring Configurations:** Includes **rotary, stationary, and multiple spring designs** to accommodate shaft movement, pressure variation, and ensure even face loading for consistent sealing.
- **API 682 Category 1, 2 & 3 – Type A, B, and C Designs:** Compliant with all API 682 categories and types for deployment in **light, moderate, and severe service conditions** across critical industrial applications.

➢ **DIMENSIONS FOR HIGHER SIZES AVAILABLE ON REQUEST**

Meet: Gala No. 7, KMC Compound, Behind Hotel Metro Palace, Behram Baug Road, Jogeshwari (West), Mumbai - 400 102. Maharashtra, India.
Talk: +91 - 22 6695 6111 / 6222 | Chat: +91 - 9967 80 40 92 / +91 - 8879 147 211
Write: office@gipfelengg.com / gipfelengg@gmail.com | Look: www.gipfelengg.com / www.gipfelengineering.in