Gipfel Engineering

ISO 9001-2015 CERTIFIED COMPANY

Metal Bellow Mechanical Seal
(Semi-Cartridge Design (Stationary Bellow Configuration)

TYPE : BS710



Face Materials :

- Carbon / Silicon Carbide / Tungsten Carbide

Secondary Seal :

- FKM (Viton) / EPDM / FFKM (Kalrez) / Graphite

Hardware :

- SS 316 / SS 316L / Hastelloy C-276 / Alloy 20 / Duplex

Operating Limits :

Size : 25.0 mm to 100.0 mm / 1.000" to 4.000"
Speed : 2900 rpm
Pressure : 25 bars (363 psi)
Temperature : -40 °C to +220 °C (-40 °F to +428 °F)

Application :

- Fatty Acid
- LPG Plants
- Biochemistry
- Thermic Fluid
- Hydrocarbons
- Process Industry
- Hot & Cold Media
- Hazardous Liquid
- Chemical Industry
- Oil & Gas Industry
- High Temperature
- Refining Technology
- Petrochemical Industry Etc.

Features :

- **Quick Installation & Easy Removal to reduce downtime.**
- Available in **Metric and Inch Sizes** for global compatibility
- **Semi-Cartridge Design** for easy installation and maintenance.
- **Stationary Bellows Type** for enhanced flexibility and durability.
- **Factory Assembled & Tested** to ensure reliability and performance.
- **Independent of Direction of Rotation,** offering versatile application.
- **Equipped with Flushing & Quenching Connections** for improved seal cooling and lubrication.

➢ DIMENSIONS FOR HIGHER SIZES AVAILABLE ON REQUEST

Meet: Gala No. 7, KMC Compound, Behind Hotel Metro Palace, Behram Baug Road, Jogeshwari (West), Mumbai - 400 102. Maharashtra, India.
Talk: +91 - 22 6695 6111 / 6222 | Chat: +91 - 9967 80 40 92 / +91 - 8879 147 211
Write: office@gipfelengg.com / gipfelengg@gmail.com | Look: www.gipfelengg.com / www.gipfelengineering.in