

Constant Level Oil Lubricator (for Oil-Lubricated Bearing Housings)

TYPE : OIL LUBRICATOR

Dome :

- Borosilicate Glass, 5 mm Thick / 100 ml Capacity

Body & Connector :

- Aluminium Coupling / Aluminium Base Holder / Aluminium Connector

Lock Nut & Guard :

- Stainless Steel Lock Nut / Metal Cage Guard

Operating Limits :

Size : 100 ml, 1/4" BSP connection

Speed : Not applicable

Pressure : On request

Temperature : On request

Application :

- Centrifugal Process Pump Bearing Housings
- Blowers & Fans with Oil-Bath Bearings
- Other Oil-Lubricated Rotating Equipment



Constant Level Oil Lubricator (for Oil-Lubricated Bearing Housings)

Features :

- **Constant Level Oiler** keeps the bearing housing oil at a fixed level.
- **Borosilicate Glass Dome** (100 ml, 5 mm thick) for at-a-glance level checks.
- **Metal Cage Guard** protects the glass dome from impact.
- **Aluminium Coupling, Base & Connector** with a stainless steel lock nut.
- **1/4" BSP Connection** to the bearing housing.
- **Oil Level** should be visible in the middle of the oiler.
- **Clean Oil Only**; no foreign substances, acids, resins or water.

➤ **DIMENSIONS ON REQUEST**