Gipfel Engineering

ISO 9001-2015 CERTIFIED COMPANY

Gas (dry gas) Seal
(Advanced Non-Contact Sealing Technology)

TYPE : GS780



Face Materials :

- Carbon / Silicon Carbide / Tungsten Carbide

Secondary Seals :

- FKM (Viton) / EPDM / FFKM (Kalrez)

Hardware :

- SS 316 / Hastelloy C-276 / Alloy 20 / Duplex / Titanium

Operating Limits :

Size : 20.0 mm to 200.0 mm / 0.750" to 8.000"
Speed : 3600 rpm
Pressure : 20 bars (290 psi)
Temperature : -20 °C to +220 °C (-4 °F to +428 °F)

Application :

- Blower
- Gas compressor
- Gas and liquid
- Centrifugal pump
- Hazardous media
- Chemical industry
- Refining technology
- Low viscosity liquid pumps
- Environmental harmful media
- Media which require high purity

Meet: Gala No. 7, KMC Compound, Behind Hotel Metro Palace, Behram Baug Road, Jogeshwari (West), Mumbai - 400 102. Maharashtra, India.
Talk: +91 - 22 6695 6111 / 6222 | Chat: +91 - 9967 80 40 92 / +91 - 8879 147 211
Write: office@gipfelengg.com / gipfelengg@gmail.com | Look: www.gipfelengg.com / www.gipfelengineering.in

Gipfel®
Engineering
ISO 9001-2015 CERTIFIED COMPANY

Gas Seal
(Advanced Non-Contact Sealing Technology)

key Features :

- **Leakage Control:** Effectively minimizes gas leakage, improving system reliability.
- **High Efficiency:** Reduces power loss and eliminates the need for liquid lubrication.
- **Factory Assembled & Tested:** Ensures reliability and performance before installation.
- **Multiple Spring Type:** Ensures uniform face loading for consistent sealing performance.
- **Cartridge Construction:** Pre-assembled unit for simplified installation and maintenance.
- **Hydraulically Balanced Type:** Reduces face load and minimizes wear, extending seal life.
- **Metric and Inch Sizes Available:** Compatible with a wide range of equipment specifications.
- **Independent of Unidirectional Rotation:** Functions effectively regardless of shaft rotation direction.
- **Rotary & Stationary Spring:** Designed for flexibility in various installation and operational conditions.
- **Quick Install & Easy Removal:** Streamlined design allows for fast maintenance and reduced downtime.
- **Supplied with Buffer Gas Supply System:** Ensures optimal sealing performance and prevents contamination.
- **Single & Double Seal:** Available in both configurations to suit different pressure and containment requirements.
- **Application in High-Speed Machinery:** Ideal for turbo compressors, centrifugal compressors, and other rotating equipment.
- **Non-contacting Design:** Utilizes aerodynamic or hydrostatic forces to maintain a gap between the sealing surfaces, minimizing friction and wear.
- **Material Compatibility:** Made from high-performance materials such as carbon, ceramics, and specialized metals to withstand harsh operating conditions.

➢ DIMENSIONS FOR HIGHER SIZES AVAILABLE ON REQUEST

Meet: Gala No. 7, KMC Compound, Behind Hotel Metro Palace, Behram Baug Road, Jogeshwari (West), Mumbai - 400 102. Maharashtra, India.
Talk: +91 - 22 6695 6111 / 6222 | Chat: +91 - 9967 80 40 92 / +91 - 8879 147 211
Write: office@gipfelengg.com / gipfelengg@gmail.com | Look: www.gipfelengg.com / www.gipfelengineering.in