Gipfel Engineering

ISO 9001-2015 CERTIFIED COMPANY

RETAINER TYPE SINGLE SPRING MECHANICAL SEAL

TYPE : SS130 / SS135



Face Materials :

- Carbon / Ceramic / Silicon Carbide / Tungsten Carbide

Elastomers:

- Nitrile (NBR) / Viton (FKM) / EPDM / Aflas / PTFE

Hardware :

- SS 304 / SS 316 / Hastelloy – C 276

Operating Limits :

Size : 12 mm to 100 mm / 0.500" to 4.000"
Speed : 2900 rpm
Pressure : 12 bars (174 psi)
Temperature : -20 °C to +120 °C (-4 °F to +248 °F)

Application :

- Viscous
- Solidifying
- Abrasive Slurries
- Hazardous Duties
- General Chemical
- Crystallizing Slurry
- Suspended Solid Slurry
- Saturated Chemical Slurry

Features :

- Single seal
- Pusher type
- Internal mounted
- Single helical coil spring
- Balanced & Unbalanced design
- Independent of the direction of rotation
- Excellent chemical compatibility due to PTFE elastomer

Meet: Gala No. 7, KMC Compound, Behind Hotel Metro Palace, Behram Baug Road, Jogeshwari (West), Mumbai - 400 102. Maharashtra, India.
Talk: +91 - 22 6695 6111 / 6222 | Chat: +91 - 9967 80 40 92 / +91 - 8879 147 211
Write: office@gipfelengg.com / gipfelengg@gmail.com | Look: www.gipfelengg.com / www.gipfelengineering.in